

Passion for Homes and Families







STANDARD FEATURES

- **1. 6**" **Multi-chambered**, **fusion welded vinyl frame** will never rot and allows for seamless installation.
- 2. Operable and fixed panels are reinforced to maximize structural integrity while also improving security.
- Both panels fully interlock when closed engaging multiple layers of weatherstripping for a tightly sealed unit.
- **4. Dual or triple pane tempered glass options** customize efficiency level.
- **5.** Heavy-Duty rollers glide on our low-profile monorail track making operation smooth and quiet.
- Elegant interior and exterior color matched handles are available with an optional keyed lock.
- 7. Heavy duty adjustable extruded screen stays rigid and glides easily in a dedicated track without bending or warping.
- **8.** Low-profile threshold allows for smooth passage.
- **9.** Order **left or right operable door** to meet any need.
- **10. Limited lifetime transferable warranty** includes coverage of all hardware, vinyl, glass, and screen.







STANDARD SIZES

NOMINAL SIZE	DOOR SIZE
5068	58-3/4″ x 79-1/2″
6068	70-3/4" x 79-1/2"
8068	94-3/4″ x 79-1/2″

Custom sizes also available

MODERN PERFORMANCE

A CLEAR VIEW WITH UNMATCHED FEATURES





THERMAL PERFORMANCE DATA

GLASS TYPE	U-VALUE	SHGC	VLT
Clear	.46	.64	.66
IntelliGlass X	.28	.23	.50
IntelliGlass X3	.26	.21	.46

Available with glass packages that meet Energy Star requirements for all regions.


HOW DOES LOW-E GLASS WORK?

Low Emissivity (Low-E) glass is one of the cornerstones of any energy efficient window. Its primary purpose is managing radiation, whether it's solar, light, ultraviolet, or heat. The secret is two or three microscopic layers of silver, which reflect heat back to its source. Other layers in the Low-E coating filter ultraviolet and solar radiation, while allowing visible light through.

Glass packages are filled with either argon gas in between the panes of glass. Argon gas is denser than air, so it makes it more difficult for heat or cold to transmit through the glass units. We use high quality sealants, sophisticated filling equipment and a voluntary verification system to ensure consistent glass performance.



CHOOSE YOUR PERFECT LOOK



ELG 08-23 Information accurate at time of printing.P roduct subject to change. ©2023 Vinylmax LLC

WINDOW+DOOR

MANUFACTURERS

2921 McBride Court Hamilton, OH 45011 (800) 847-3736 vinylmax.com

Fenestration & Glazing Industry Alliance